#### (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

### (19) World Intellectual Property Organization

International Bureau



# I IBBIR BINGIRI II BIRNE NEN BENI BENI BENI I IN IN BENIR IRNI BIRBE NENE IRNI BIRI BIN BIRBEN IRIB NEN IRE I

#### (43) International Publication Date 13 October 2005 (13.10.2005)

#### **PCT**

# (10) International Publication Number WO 2005/094296 A2

(51) International Patent Classification: Not classified

(21) International Application Number:

PCT/US2005/010302

(22) International Filing Date: 28 March 2005 (28.03.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(**30**) **Priority Data:** 60/556,577

26 March 2004 (26.03.2004) Us

(71) Applicant (for all designated States except US): ACTU-ANT CORPORATION [US/US]; 720 West James Street, Columbus, WI 53925 (US).

(72) Inventors; and


(75) Inventors/Applicants (for US only): GONZALEZ, Jesus [ES/ES]; Costa Azul St., 17, E-28440 Guadarrama (ES).

**SORDO, Luis** [ES/ES]; Calle San Jose Artesano N.8, E-28108 Alcobendas (ES).

- (74) Agent: RADLER, Daniel, G.; Quarles & Brady LLP, 411 East Wisconsin Avenue, Milwaukee, WI 53202 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: HYDRAULIC AUXILIARY HOIST AND CRANE CONTROL FOR HIGH PRECISION LOAD POSITIONING



(57) Abstract: A hoist for positioning a load includes a plurality of lift cylinders, a plurality of position sensors, a plurality of electronically controlled valves, a user input device, and a hoist controller. Each of the hydraulic hoist cylinders is coupled at one end to the hoist and at an opposite end to the load at a lifting point. Each of the position sensors is associated with one of the hoist cylinders and operable to provide position data for the associated hoist cylinder. The electronically controlled valves are hydraulically coupled to the hoist cylinders for extending and retracting the associated hoist cylinders. The user input device is operable by a user to specify load data. The hoist controller is operable to receive the load data from the input device and the position data from the position sensors and in response thereto to control the electronically controlled valves so as to position the load according to the load data.

## WO 2005/094296 A2

FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

#### Published:

 without international search report and to be republished upon receipt of that report